



SOUTHERN RACING FUELS, INC.

121 N. JENKINS RD. FORT PIERCE | FLORIDA 34947
PH. (877) 240-3278



STANDARD™

Sunoco® Standard™ is a 110 octane leaded race fuel that is commonly used in all forms of motorsports. It features a comprehensive additive package to enhance shelf life by improving stability and minimizing oxidation. Sunoco Standard is designed for compression ratios up to about 13:1 in conventional small block V8s with iron heads, and can tolerate higher compression ratios in smaller or more efficient combustion chambers. It is also a good choice for mild nitrous, turbocharged, or supercharged applications.

As with any gasoline, Sunoco Standard should be stored in opaque, tightly sealed containers and kept where temperatures are stable. Properly stored, the shelf life of Sunoco Standard is in excess of 2 years.

Disclaimer: Legal in California only for racing vehicles in sanctioned racing events.

Legal: For off-road and racing applications only.

SUNOCO LEADED RACE FUELS - PDS

APPLICATIONS

- Road Course
- Asphalt Oval
- Dirt Oval
- Off-road
- Rally
- Drag
- Truck and Tractor Pulling
- Motorcycle Road Course
- Off-road Motorcycle and ATV
- Karts
- Boats and Personal Watercraft
- Snowmobiles
- Muscle Cars and Vintage Cars
- Miscellaneous Nitrous, Superchargers, Turbochargers

TECHNICAL DETAILS

Color	Purple
Octane (R+M)/2	110
Research Octane	114
Motor Octane	106
Specific Gravity	0.728
Weight (lbs/gallon)	6.1
Reid Vapor Pressure	5.6
10% Evaporation	149
50% Evaporation	214
90% Evaporation	255
Final Boiling Point	387
Stoichiometric Air/Fuel Ratio	15
Oxygen (weight %)	0
Ethanol (volume %)	0
HC Ratio	2.06
Lower Heating Value (Btu/Gallon)	113400
Lower Heating Value (Btu/Pound)	18700
Dielectric Constant	-0.2
Leaded	Yes