



SOUTHERN RACING FUELS, INC.

121 N. JENKINS RD. FORT PIERCE | FLORIDA 34947
PH. (877) 240-3278



MO2X Leaded

Sunoco MO2X is an oxygenated racing fuel designed for excellent throttle response in high compression, high rpm 2- and 4-stroke applications such as motorcycles, all-terrain vehicles, snowmobiles, and karts. It complies with sanctioning body fuel rules limiting oxygen content to 2.8 weight %. MO2X does not have to be drained from the fuel system after each use.

Sunoco MO2X contains additives to enhance storage life. It is not a street legal fuel and is for off-road and racing use only. As with any gasoline, it should be stored in opaque sealed containers where temperatures are stable.

Disclaimer: Legal in California only for racing vehicles in sanctioned racing events.

Legal: For off-road and racing applications only.

SUNOCO LEADED RACE FUELS - PDS

APPLICATIONS

- Motorcycle Road Course
- Off-road Motorcycle and ATV
- Karts
- Snowmobiles

TECHNICAL DETAILS

Color	Dark Green
Octane (R+M)/2	112
Research Octane	116
Motor Octane	108
Specific Gravity	0.72
Weight (lbs/gallon)	6
Reid Vapor Pressure	10.1
Initial Boiling Point	84
10% Evaporation	116
50% Evaporation	192
90% Evaporation	229
Final Boiling Point	244
Stoichiometric Air/Fuel Ratio	14.6
Oxygen (weight%)	2.7
Ethanol (volume%)	6.8
HC Ratio	2.15
OC Ratio	0.022
Dielectric Constant	5.9
Leaded	Yes